










Causa costi di gestione, agli ordini inferiori al valore di 100,00 € di sola merce, verrà addebitato un costo di 14,00 €. Ordini di importo inferiori a 50,00 € addebito pari a 19,00 €. / *For orders value less than 100,00 € (transport cost excluded), 14,00 € as extra costs charges. and 19,00 € for orders value less than 50,00 € (leftover stock deliveries excluded).*

NS. COD. CODE	COMPATIBILE COMPATIBLE	DESCRIZIONE / DESCRIPTION	DIM. EST. mm EXT. SIZE mm	IMMAGINE / IMAGE
06532		Controllore IWC 730 230V, 3 relé, 2 sonde NTC attacco standard, compressore 30A (2 HP) <i>Controller IWC 730 230V, 3 relays, 2 NTC probes, standard fitting 30A (2 HP) compressor</i>	dima foratura <i>drilling template</i> 150 x 31 profondità <i>depth</i> 60	
06170		Kit morsetti sconnettabili femmina ZZ000072 per IWC 720 (cod.06530) <i>Female disconnectable clamps Kit ZZ000072 for IWC 720 (code 06530)</i>		
06172		Kit morsetti sconnettabili femmina ZZ000073 per IWC 730 (cod.06532) <i>Female disconnectable clamps Kit ZZ000073 for IWC 730 (code 06532)</i>		
06190		Sonda standard PTC in PVC campo -30° +80° C <i>Standard PTC probe in PVC range -30° +80° C colore nero - black colour</i>	6 x 30 L=1500	
06191		Sonda standard NTC in PVC campo -30° +80° C <i>Standard NTC probe in PVC range -30° +80° C colore grigio - grey colour</i>	6 x 40 L=1500	
06192		Sonda standard NTC in PVC campo -30° +80° C <i>Standard NTC probe in PVC range -30° +80° C colore grigio - grey colour</i>	6 x 40 L=3000	
06193		Sonda standard PTC in PVC campo -30° +80° C <i>Standard PTC probe in PVC range -30° +80° C colore nero - black colour</i>	6 x 30 L=3000	
06195		Sonda <u>al silicone</u> NTC , campo -50° +110° C <i><u>Silicone</u> NTC probe, range -50° +110° C</i>	6 x 40 L=1500	
06196		Sonda <u>al silicone</u> PTC, campo -55° +150° C <i><u>Silicone</u> PTC probe, range -55° +150° C</i>	6 x 40 L=1500	
06197		Sonda <u>al silicone</u> NTC , campo -50° +110° C <i><u>Silicone</u> NTC probe, range -50° +110° C</i>	6 x 40 L=3000	
06198		Sonda <u>al silicone</u> PTC, campo -55° +150° C <i><u>Silicone</u> PTC probe, range -55° +150° C</i>	6 x 40 L=3000	

Causa costi di gestione, agli ordini inferiori al valore di 100,00 € di sola merce, verrà addebitato un costo di 14,00 €. Ordini di importo inferiori a 50,00 € addebito pari a 19,00 €. / For orders value less than 100,00 € (transport cost excluded), 14,00 € as extra costs charges. and 19,00 € for orders value less than 50,00 € (leftover stock deliveries excluded).

NS. COD. CODE	COMPATIBILE COMPATIBLE	DESCRIZIONE / DESCRIPTION	DIM. EST. mm EXT. SIZE mm	IMMAGINE / IMAGE
06181		Sonda NTC in TPE STEEL (<u>capsula inox</u>), campo -50° +110° C - IP68 (stagna) nera <i>NTC probe in TPE STEEL, (<u>stainless steel capsule</u>) range -50° +110° C - IP68 (water tight) black</i>	6 x 30 L=1500	
06180		Sonda PTC in TPE STEEL (<u>capsula inox</u>), campo -50° +110° C - IP68 (stagna) nera <i>PTC probe in TPE STEEL, (<u>stainless steel capsule</u>) range -50° +110° C - IP68 (water tight) black</i>	6 x 40 L=1500	
06183		Sonda NTC in TPE STEEL (<u>capsula inox</u>), campo -50° +110° C - IP68 (stagna) nera <i>NTC probe in TPE STEEL, (<u>stainless steel capsule</u>) range -50° +110° C - IP68 (water tight) black</i>	6 x 40 L=3000	
06182		Sonda PTC in TPE STEEL (<u>capsula inox</u>), campo -50° +110° C - IP68 (stagna) nera <i>PTC probe in TPE STEEL, (<u>stainless steel capsule</u>) range -50° +110° C - IP68 (water tight) black</i>	6 x 40 L=3000	
06184		Sonda NTC in TPE (capsula in plastica) campo -40° +110° C - IP 68 (stagna) nera <i>NTC probe in TPE (plastic capsule) range -40° +110° C - IP 68 (watertight) black</i>	5 x 20 L=1500	
06185		Sonda PTC in TPE (capsula in plastica) campo -40° +110° C - IP 68 (stagna) nera <i>PTC probe in TPE (plastic capsule) range -40° +110° C - IP 68 (watertight) black</i>	5 x 20 L=1500	
06186		Sonda NTC in TPE (capsula in plastica) campo -40° +110° C - IP 68 (stagna) nera <i>NTC probe in TPE (plastic capsule) range -40° +110° C - IP 68 (watertight) black</i>	5 x 20 L=3000	
06187		Sonda PTC in TPE (capsula in plastica) campo -40° +110° C - IP 68 (stagna) nera <i>PTC probe in TPE (plastic capsule) range -40° +110° C - IP 68 (watertight) black</i>	5 x 20 L=3000	
06188		Sonda NTC in TPE attacco JST (capsula in plastica) campo -40° +110° C - IP 68, per controllore IWC 720 - 230V con attacco JST <i>NTC probe in TPE 5 x 20 1.5 m JST fitting (plastic capsule) range -40° +110° C - IP 68, for controller IWC 720 - 230V with JST fitting</i>	5 x 20 L=1500	
06189		Sonda NTC in TPE attacco JST (capsula in plastica) campo -40° +110° C - IP 68, per controllore IWC 720 - 230V con attacco JST <i>NTC probe in TPE 5 x 20 1.5 m JST fitting (plastic capsule) range -40° +110° C - IP 68, for controller IWC 720 - 230V with JST fitting</i>	5 x 20 L=3000	

Causa costi di gestione, agli ordini inferiori al valore di 100,00 € di sola merce, verrà addebitato un costo di 14,00 €. Ordini di importo inferiori a 50,00 € addebito pari a 19,00 €. / For orders value less than 100,00 € (transport cost excluded), 14,00 € as extra costs charges. and 19,00 € for orders value less than 50,00 € (leftover stock deliveries excluded).

NS. COD. CODE	COMPATIBILE COMPATIBLE	DESCRIZIONE / DESCRIPTION	DIM. EST. mm EXT. SIZE mm	IMMAGINE / IMAGE
06176		Sonda NTC in PVC, campo -30° +80° C per controllore IWC 720 <u>con attacco Faston</u> <i>NTC probe in PVC, range -30° +80° C for controller IWC 720 - 230V with Faston fitting</i>	6 x 40 L=1500	
06178		Sonda NTC in silicone , campo -50° +110° C per controllore IWC 720 <u>con attacco Faston</u> <i>NTC probe in silicone, range -50° +110° C for controller IWC 720 - 230V with Faston fitting</i>	6 x 40 L=1500	