





Causa costi di gestione, agli ordini inferiori al valore di 100,00 euro di sola merce, verrà addebitato un costo di 14,00 euro. Ordini di importo inferiori a 50,00 euro addebito pari a 19,00 euro. / For orders value less than 100,00 euro (transport cost excluded), 14,00 euro as extra costs charges, and 19,00 euro for orders value less than 50,00 euro (leftover stock deliveries excluded).

NS. COD. CODE	COMPATIBILE COMPATIBLE	DESCRIZIONE DESCRIPTION	DIM. EST mm EXT SIZE mm	IMMAGINE IMAGE	
06532		Controllore IWC 730 230V, 3 relé, 2 sonde NTC attacco standard, compressore 30A (2 HP) <i>Controller IWC 730 230V, 3 relays, 2 NTC probes, standard fitting 30A (2 HP) compressor</i>	dima foratura <i>drilling template</i> 150 x 31 profondità <i>depth</i> 60		
06170		Kit morsetti sconnettibili femmina ZZ000072 per IWC 720 (cod.06530) <i>Female disconnectable clamps Kit ZZ000072 for IWC 720 (code 06530)</i>			
06172		Kit morsetti sconnettibili femmina ZZ000073 per IWC 730 (cod.06532) <i>Female disconnectable clamps Kit ZZ000073 for IWC 730 (code 06532)</i>			
06190		Sonda standard PTC in PVC campo -30° +80° C <i>Standard PTC probe in PVC range -30° +80° C</i> colore nero – <i>black colour</i>	6 x 30 L=1500		
06191		Sonda standard NTC in PVC campo -30° +80° C <i>Standard NTC probe in PVC range -30° +80° C</i> colore grigio – <i>grey colour</i>	6 x 40 L=1500		
06192		Sonda standard NTC in PVC campo -30° +80° C <i>Standard NTC probe in PVC range -30° +80° C</i> colore grigio – <i>grey colour</i>	6 x 40 L=3000		
06193		Sonda standard PTC in PVC campo -30° +80° C <i>Standard PTC probe in PVC range -30° +80° C</i> colore nero – <i>black colour</i>	6 x 30 L=3000		
06195		Sonda al silicone NTC, campo -50° +110° C <i>Silicone NTC probe, range -50° +110° C</i>	6 x 40 L=1500		
06196		Sonda al silicone PTC, campo -55° +150° C <i>Silicone PTC probe, range -55° +150° C</i>	6 x 40 L=1500		
06197		Sonda al silicone NTC, campo -50° +110° C <i>Silicone NTC probe, range -50° +110° C</i>	6 x 40 L=3000		
06198		Sonda al silicone PTC, campo -55° +150° C <i>Silicone PTC probe, range -55° +150° C</i>	6 x 40 L=3000		

Causa costi di gestione, agli ordini inferiori al valore di 100,00 euro di sola merce, verrà addebitato un costo di 14,00 euro. Ordini di importo inferiori a 50,00 euro addebito pari a 19,00 euro. / For orders value less than 100,00 euro (transport cost excluded), 14,00 euro as extra costs charges, and 19,00 euro for orders value less than 50,00 euro (leftover stock deliveries excluded).

NS. COD. CODE	COMPATIBILE COMPATIBLE	DESCRIZIONE DESCRIPTION	DIM. EST mm EXT SIZE mm	IMMAGINE IMAGE	
06181		Sonda NTC in TPE STEEL (capsula inox), campo -50° +110° C - IP68 (stagna) nera <i>NTC probe in TPE STEEL, (stainless steel capsule) range -50° +110° C - IP 68 (watertight) black</i>	6 x 40 L=1500		
06180		Sonda PTC in TPE STEEL (capsula inox), campo -50° +110° C - IP68 (stagna) nera <i>PTC probe in TPE STEEL, (stainless steel capsule) range -50° +110° C - IP68 (watertight) black</i>	6 x 40 L=1500		
06183		Sonda NTC in TPE STEEL (capsula inox), campo -50° +110° C - IP68 (stagna) nera <i>NTC probe in TPE STEEL, (stainless steel capsule) range -50° +110° C - IP 68 (watertight) black</i>	6 x 40 L=3000		
06182		Sonda PTC in TPE STEEL (capsula inox), campo -50° +110° C - IP68 (stagna) nera <i>PTC probe in TPE STEEL, (stainless steel capsule) range -50° +110° C - IP68 (watertight) black</i>	6 x 40 L=3000		
06184		Sonda NTC in TPE (capsula in plastica) campo -40° +110° C - IP 68 (stagna) nera <i>NTC probe in TPE (plastic capsule) range -40° +110° C - IP 68 (watertight) black</i>	5 x 20 L=1500		
06185		Sonda PTC in TPE (capsula in plastica) campo -40° +110° C - IP 68 (stagna) nera <i>PTC probe in TPE (plastic capsule) range -40° +110° C - IP 68 (watertight) black</i>	5 x 20 L=1500		
06186		Sonda NTC in TPE (capsula in plastica) campo -40° +110° C - IP 68 (stagna) nera <i>NTC probe in TPE (plastic capsule) range -40° +110° C - IP 68 (watertight) black</i>	5 x 20 L=3000		
06187		Sonda PTC in TPE (capsula in plastica) campo -40° +110° C - IP 68 (stagna) nera <i>PTC probe in TPE (plastic capsule) range -40° +110° C - IP 68 (watertight) black</i>	5 x 20 L=3000		
06188		Sonda NTC in TPE attacco JST (capsula in plastica) campo -40° +110° C - IP 68, per controllore IWC 720 - 230V con attacco JST <i>NTC probe in TPE 5 x 20 1.5 m JST fitting (plastic capsule) range -40° +110° C - IP 68, for controller IWC 720 - 230V with JST fitting</i>	5 x 20 L=1500		
06189		Sonda NTC in TPE attacco JST (capsula in plastica) campo -40° +110° C - IP 68, per controllore IWC 720 - 230V con attacco JST <i>NTC probe in TPE 5 x 20 1.5 m JST fitting (plastic capsule) range -40° +110° C - IP 68, for controller IWC 720 - 230V with JST fitting</i>	5 x 20 L=3000		

Causa costi di gestione, agli ordini inferiori al valore di 100,00 euro di sola merce, verrà addebitato un costo di 14,00 euro. Ordini di importo inferiori a 50,00 euro addebito pari a 19,00 euro. / For orders value less than 100,00 euro (transport cost excluded), 14,00 euro as extra costs charges, and 19,00 euro for orders value less than 50,00 euro (leftover stock deliveries excluded).

NS. COD. CODE	COMPATIBILE COMPATIBLE	DESCRIZIONE DESCRIPTION	DIM. EST mm EXT SIZE mm	IMMAGINE IMAGE	
06176		Sonda NTC in PVC, campo -30° +80° C per controllore IWC 720 con attacco Faston <i>NTC probe in PVC, range -30° +80° C for controller IWC 720 - 230V with Faston fitting</i>	6 x 40 L=1500		
06178		Sonda NTC in silicone , campo -50° +110° C per controllore IWC 720 <u>con attacco Faston</u> <i>NTC probe <u>in silicone</u>, range -50° +110° C for controller IWC 720 - 230V <u>with Faston fitting</u></i>	6 x 40 L=1500	